

# **PRODUCT SPECIFICATION** **FOR LCD MODULE**

**Revision:** 1.0

**Model No:** LS013I05-S-V1

**Module Type:** COG+FPC+B/L

<b>APPROVED SIGNATURE</b>
---------------------------

- Approved Product Specification only
- Approved Product Specification and Samples

<b><u>Prepared By</u></b>	<b><u>Checked By</u></b>	<b><u>Approved By</u></b>

# Contents

目录

1. General Description .....	3
2. Physical Features .....	3
3. Mechanical Specification .....	3
4. Outline Dimension .....	4
5. Absolute Maximum Ratings .....	5
6. Electrical Characteristics .....	5
7. Module Function Description .....	6
8. Electro-Optical Characteristics .....	10
9. Inspection Standards .....	13
10. Records Of Version .....	19

# 1. General Description

LS013I05-S-V1 is a transmissive type a-Si TFT-LCD (amorphous silicon thin film transistor liquid crystal display) module, which is composed of a TFT-LCD panel, a driver circuit and a backlight unit. The panel size is 1.3 inch and the resolution is 240(RGB)\*240, the panel can display up to 262k colors.

# 2. Physical Features

Display Mode	TFT-LCD Module
	Active matrix TFT, Transmissive type
Display Format	Graphic 240(RGB)×240 Dot-matrix
Input Data	SPI
Viewing Direction (Grayscale Inversion)	IPS
Drive	ST7789P3

# 3. Mechanical Specification

Item	Specification	Unit
Module size (H×V×D)	26.2 ×29.3×1.97	mm
Number of dots	240(RGB) ×240	pixel
Active area (H×V)	23.4×23.4	mm



## 5. Absolute Maximum Ratings


Item	Symbol	Min	Max	Unit	Remark
Supply voltage	VCC	-0.3	4.6	V	Note1 Note2
Supply voltage	IOVCC	-0.3	4.0	V	
Operating temperature	TOPR	-20	70	°C	
Storage temperature	TSTR	-30	80	°C	

## 6. Electrical Characteristics

Item	Symbol	Rating			Unit	Remark	
		Min	Typ	Max			
Supply voltage	VCC	2.4	2.8	3.3	V	Note1	
Supply voltage	IOVCC	1.65	1.8	3.3	V		
Input Voltage	L level	VIL	0	---	0.3*IOVCC		V
	H level	VIH	0.7*IOVCC	---	IOVCC		V

## 7. Module Function Description

### 7-1. Block Diagram Of LCM



## 7-2. Pin Description

<b>PIN NO.</b>	<b>Symbol</b>	<b>I/O</b>	<b>Description</b>
1	LEDK	P	Back light cathode -
2	LEDA/VDD	P	Power supply
3	GND	P	Ground
4	DC	I	Display data/command selection pin
5	CS	I	Chip select pin
6	SCL	I	serial interface clock
7	SDA	I	Serial data input
8	RST	I	Reset signal

## 7-3 Timing Characteristics

### 7.4.2 Serial Interface Characteristics (3-line serial):




Figure 4 3-line serial Interface Timing Characteristics

VDDI=1.65 to 3.3V, VDD=2.4 to 3.3V, AGND=DGND=0V, Ta=25 °C


Signal	Symbol	Parameter	Min	Max	Unit	Description
CSX	T <sub>CSS</sub>	Chip select setup time (write)	TBD	-	ns	
	T <sub>CSH</sub>	Chip select hold time (write)	TBD	-	ns	
	T <sub>CSS</sub>	Chip select setup time (read)	TBD	-	ns	
	T <sub>SCC</sub>	Chip select hold time (read)	TBD	-	ns	
	T <sub>CHW</sub>	Chip select "H" pulse width	TBD	-	ns	
SCL	T <sub>SCYCW</sub>	Serial clock cycle (Write)	TBD	-	ns	
	T <sub>SHW</sub>	SCL "H" pulse width (Write)	TBD	-	ns	
	T <sub>SLW</sub>	SCL "L" pulse width (Write)	TBD	-	ns	
	T <sub>SCYCR</sub>	Serial clock cycle (Read)	TBD	-	ns	
	T <sub>SHR</sub>	SCL "H" pulse width (Read)	TBD	-	ns	
	T <sub>SLR</sub>	SCL "L" pulse width (Read)	TBD	-	ns	
SDA (DIN)	T <sub>SDS</sub>	Data setup time	TBD	-	ns	
	T <sub>SDH</sub>	Data hold time	TBD	-	ns	
DOUT	T <sub>ACC</sub>	Access time	TBD	TBD	ns	For maximum CL=30pF
	T <sub>OH</sub>	Output disable time	TBD	TBD	ns	For minimum CL=8pF

Table 5 3-line serial Interface Characteristics

Note 1 : The rising time and falling time (Tr, Tf) of input signal are specified at 15 ns or less. Logic high and low levels are specified as 30% and 70% of VDDI for Input signals.

Note 2 : In the read sequence of Serial interface, the 500nsec delay time is needed between read command and first read clock.

The power on/off sequence is illustrated below



## 8. Electro-Optical Characteristics

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Response time		Tr +Tf	$\theta_x = \theta_y = 0$	---	35	40	ms	Note 1
Contrast Ratio		CR		640	800	---	---	Note 2
Transmittance		T%		4	4.5	---	%	
Color Chromaticity (CIE1931)	White	W x	$\theta_x = \theta_y = 0$	---	0.315	---	---	
		W y		---	0.340	---	---	
Viewing angle	$\theta_T$		CR > 10	---	80	---	Deg.	Note 3
	$\theta_B$			---	80	---		
	$\theta_L$			---	80	---		
	$\theta_R$			---	80	---		


### 4.2 Measuring Condition

- Measuring surrounding : dark room
- Ambient temperature :  $25 \pm 2^\circ\text{C}$
- 15min. warm-up time.

### 4.3 Measuring Equipment

FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.


Note (1) Definition of Viewing Angle:




Note (2) Definition of Contrast Ratio (CR):  
measured at the center point of panel

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$


Note (3) Definition of Response Time: Sum of  $T_R$  and  $T_F$



Note (4) Definition of optical measurement setup



### Note(4) Backlight circuit



# 9. Inspection Standards

## 1. AQL(Acceptable Quality Level)

AQL of major and minor defect


According to GB/T 2828-2003 ; , normal inspection, Class II

MAJOR DEFECT	MINOR DEFECT
0.65	1.5

## 2. Basic conditions for inspection

The LCM face to us, in normal environment, About an angle of incidence 30, a distance of 30cm with normal eye, with an angle of 45 degree to check the products without uncovering the film!

(As shown below)






## 3. Inspection item and criteria

### 3.1 Visual inspection criterion in immobility




#### 3.1.1 Glass defect

No	Defect item	Criteria	Remark
1	Dimension Unconformity  (Major defect)	By Engineering Drawing	

No	Defect item	Criteria	Remark
2	Cracks  (Major defect)	1.Linear cracks on panel <b>【 Reject 】</b> 2. Nonlinear crack contrast by limited sample	
3	Glass extrude the conductive area  (minor defect)	a: disregards and no influence assemblage 1) $b \leq 1/3$ Pin width(non bonding area) <b>【 Accept 】</b> 2) bonding area $\leq 0.5\text{mm}$ <b>【 Accept 】</b>	a:Length, b:Width
4	Pin-side · conductive area damaged  (minor defect)	(a c : disregards) $b \leq 1/3$ of effective length for bonding electrode  <b>【 Accept 】</b>	a:Length·b:Width·c:Thickness 
5	Pin-side · non-conductive area damaged  (minor defect)	1) Damage area don't touch the ITO (Inclueing contraposition mark,except scribing mark ) <b>【 Accept 】</b> 2) $c < T$ $b \leq BM$ 1/3 of width <b>【 Accept 】</b> 3) $c = T$ b not touch the seal glue <b>【 Accept 】</b> 4) a disregards	a:Length·b:Width·c:Thickness 

No	Defect item	Criteria	Remark
6	Non-pin-side damage  (minor defect)	$c < T$  1) $b$ exceeds $1/3$ BM	$c$ : Thickness $b$ : width of damage  
		$c = T$ $b$ not touch the seal glue  <b>【Reject】</b>  <b>【Reject】</b>	

### 3.1.2 LCD appearance defect (View area)

No	Defect item	Criteria		Remark
1	Fiber · glass crack · polarizer scratch/folded  (minor defect)	Specification	Allowable	note1: $L$ : Length · $W$ : Width note2: disregard if out of AA 
		$0.05\text{mm} < W \leq 0.1\text{mm};$ $L \leq 3.0\text{mm}$	1	
		$W > 0.1\text{mm}; L > 3.0\text{mm}$	0	
2	Polarizer bubble · concave and convex  (minor defect)	$\psi \leq 0.2\text{mm}$	disregard	note 1: $\psi = (L+W)/2$ ; $L$ : Length · $W$ : Width note2: disregard if out of AA 
		$0.2\text{mm} < \psi \leq 0.3\text{mm}$	2	
		$0.3\text{mm} < \psi \leq 0.5\text{mm}$	1	
		$0.5\text{mm} < \psi$	0	
3	Black dots · dirty dots · impurities · eyewinker  (Major defect)	$\psi \leq 0.15\text{mm}$	disregard	note2: disregard if out of AA 
		$0.15\text{mm} < \psi \leq 0.25\text{mm}$	2	
		$0.25\text{mm} < \psi \leq 0.3\text{mm}$	1	
		$0.3\text{mm} < \psi$	0	
4	Polarizer prick  (Major defect)	$\psi \leq 0.1\text{mm}$	disregard	note1: $\psi = (L+W)/2$ ; $L$ = Length · $W$ = Width note2: the distance between two dots $> 5\text{mm}$
		$0.1\text{mm} < \psi \leq 0.25\text{mm}$	3	
		$\psi > 0.25\text{mm}$	0	

### 3.1.3 .FPC


No	Defect item	Criteria		Remark
1	Copper screen peel (Major defect)	Copper screen peel 【Reject】		
2	No release tape or peel (Major defect)	No release tape or peel 【Reject】		
3	Dirty dot and impurity of FPC for customer using side (minor defect)	Specification	Allowable	note1: Cannot have stride ITO impurities
		$\psi \leq 0.25\text{mm}$	2	
		$\psi > 0.25$	0	

### 3.1.4 Black tape & Mara tape

1	FPC or H/S black tape shift  (minor defect)	1.shift spec: 1)glue to the polarize 【Reject】 2) IC bare 【Reject】 2. left-and-right spec: 1) exceed of FPC edge or H-S edge 【Reject】 2)IC bare 【Reject】	
2	No black tape (Major defect)	No black tape 【Reject】	
3	Tape position mistake (minor defect)	Not by engineering drawing 【Reject】	
4	Mara tape defect  (minor defect)	Peel before pulling the protecting film. 【Reject】	



### 3.1.5 Silicon and Tuffy glue

No	Defect item	Criteria	Remark
1	Quantity of silicon (minor defect)	Uncover the ITO and circuit area. 【Reject】	note: compared by engineering drawing.

No	Defect item	Criteria	Remark
2	Tuffy glue (minor defect)	1. Uncover the reveal copper area <b>【 Reject 】</b> 2. Cover layer 0.3mm(Min) ~ 3.0mm(Max) <b>【 accept 】</b>	note:if customer has special requirement , refer to the technical document. 
3	Depth of glue covering (minor defect)	Depth of glue covering overtop front Polarizer <b>【 Reject 】</b>	Except of the special requirement -

### 3.2 Electrical criteria

No	Defect item	Criteria	Remark
1	No display (Major defect)	No display <b>【 Reject 】</b>	
2	Missing line (Major defect)	Missing line <b>【 Reject 】</b>	
3	Seg-com light and dark (Major defect)	Seg-com light and dark <b>【 Reject 】</b>	ND filter 2% test
4	No display in immobility (Major defect)	No display in immobility <b>【 Reject 】</b>	
5	Flicker of Pattern (Major defect)	Flicker of Pattern <b>【 Reject 】</b>	
6	Mura (Major defect)	ND filter 2% test	
7	Over current (Major defect)	Over current <b>【 Reject 】</b>	
8	Voltage out of specification (Major defect)	Voltage out of specification <b>【 Reject 】</b>	
9	Pattern blur ,error code (Major defect)	Pattern blur ,error code <b>【 Reject 】</b>	
10	Dark light, Flicker (Major defect)	Dark light, Flicker <b>【 Reject 】</b>	

No	Defect item	Criteria	Allowable	Remark
11	Black/White dots · Dirty dots · eyewinker  (Major defect)	Specification	Allowable	Note1: disregard if out of AA  
		$\psi \leq 0.15\text{mm}$	disregard	
		$0.15\text{mm} < \psi \leq 0.25\text{mm}$	2	
		$0.25\text{mm} < \psi \leq 0.3\text{mm}$	1	
		$0.3\text{mm} < \psi$	0	
12	Fiber · glass cratch · polarizer scratch/folded  (minor defect)	$W \leq 0.03\text{mm}$	disregard	note1: L : Length · W : Width note2: disregard if out of AA  
		$0.03\text{mm} < W \leq 0.05\text{mm}$ ; $L \leq 3.0\text{mm}$	2	
		$0.05\text{mm} < W \leq 0.1\text{mm}$ ; $L \leq 3.0\text{mm}$	1	
		$W > 0.1\text{mm}$ ; $L > 3.0\text{mm}$	0	

